



N-Channel Enhancement Mode Field Effect Transistor

FEATURES

- 20V, 8A, $R_{DS(ON)} = 20m\Omega$ @ $V_{GS} = 4.5V$.
 $R_{DS(ON)} = 28m\Omega$ @ $V_{GS} = 2.5V$.
- Super High dense cell design for extremely low $R_{DS(ON)}$.
- High power and current handing capability.
- RoHS compliant.



ABSOLUTE MAXIMUM RATINGS

 $T_A = 25^\circ C$ unless otherwise noted

Parameter	Symbol	Limit	Units
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 12	V
Drain Current-Continuous	I_D	8	A
Drain Current-Pulsed ^a	I_{DM}	32	A
Maximum Power Dissipation	P_D	2.0	W
Operating and Store Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ C$

Thermal Characteristics

Parameter	Symbol	Limit	Units
Thermal Resistance, Junction-to-Ambient ^b	$R_{\theta JA}$	62.5	$^\circ C/W$



CEC2308

Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted







Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	20			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = 20\text{V}, V_{\text{GS}} = 0\text{V}$			1	μA
Gate Body Leakage Current, Forward	I_{GSSF}	$V_{\text{GS}} = 12\text{V}, V_{\text{DS}} = 0\text{V}$			10	uA
Gate Body Leakage Current, Reverse	I_{GSSR}	$V_{\text{GS}} = -12\text{V}, V_{\text{DS}} = 0\text{V}$			-10	uA
On Characteristics ^b						
Gate Threshold Voltage	$V_{\text{GS(th)}}$	$V_{\text{GS}} = V_{\text{DS}}, I_D = 250\mu\text{A}$	0.5		1.2	V
Static Drain-Source On-Resistance	$R_{\text{DS(on)}}$	$V_{\text{GS}} = 4.5\text{V}, I_D = 5\text{A}$		16.5	20	$\text{m}\Omega$
		$V_{\text{GS}} = 2.5\text{V}, I_D = 4\text{A}$		21.5	28	$\text{m}\Omega$
Dynamic Characteristics ^c						
Input Capacitance	C_{iss}	$V_{\text{DS}} = 10\text{V}, V_{\text{GS}} = 0\text{V}, f = 1.0 \text{ MHz}$		45		pF
Output Capacitance	C_{oss}			130		pF
Reverse Transfer Capacitance	C_{rss}			15		pF
Switching Characteristics ^c						
Turn-On Delay Time	$t_{\text{d(on)}}$	$V_{\text{DD}} = 10\text{V}, I_D = 6.5\text{A}, V_{\text{GS}} = 5\text{V}, R_{\text{GEN}} = 3\Omega$		0.35		μs
Turn-On Rise Time	t_r			0.8		μs
Turn-Off Delay Time	$t_{\text{d(off)}}$			2.49		μs
Turn-Off Fall Time	t_f			1.55		μs
Total Gate Charge	Q_g	$V_{\text{DS}} = 10\text{V}, I_D = 6.5\text{A}, V_{\text{GS}} = 4.5\text{V}$		3.89		nC
Gate-Source Charge	Q_{gs}			0.92		nC
Gate-Drain Charge	Q_{gd}			1.85		nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Current	I_S				1.6	A
Drain-Source Diode Forward Voltage ^b	V_{SD}	$V_{\text{GS}} = 0\text{V}, I_S = 1.5\text{A}$			1.2	V

Notes :

a Repetitive Rating : Pulse width limited by maximum junction temperature

b.Pulse Test : Pulse Width < 300 μs , Duty Cycle < 2%.

c.Guaranteed by design, not subject to production testing.

**Figure 1. Output Characteristics****Figure 2. Transfer Characteristics****Figure 3. Capacitance****Figure 4. On-Resistance Variation with Temperature****Figure 5. Gate Threshold Variation with Temperature****Figure 6. Body Diode Forward Voltage Variation with Source Current**




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area




Figure 9. Breakdown Voltage Variation VS Temperature




Figure 10. Switching Test Circuit




Figure 11. Switching Waveforms




Figure 12. Normalized Thermal Transient Impedance Curve