


N-Channel Enhancement Mode Field Effect Transistor With Fast Body Diode**FEATURES**

- 700V@ T_J max, 46A, $R_{DS(ON)} = 58m\Omega$ @ $V_{GS} = 10V$.
- Super high dense cell design for extremely low $R_{DS(ON)}$.
- High power and current handing capability.
- Pb-free lead plating ; RoHS compliant.
- Halogen Free.
- Fast reverse recovery time.
- TO-247 package.

**ABSOLUTE MAXIMUM RATINGS** $T_C = 25^\circ C$ unless otherwise noted

Parameter	Symbol	Limit	Units
Drain-Source Voltage	V_{DS}	650	V
Gate-Source Voltage	V_{GS}	± 30	V
Drain Current-Continuous @ $T_C = 25^\circ C$ @ $T_C = 100^\circ C$	I_D	46	A
		29	A
Drain Current-Pulsed ^a	I_{DM}	184	A
Maximum Power Dissipation @ $T_C = 25^\circ C$ - Derate above 25° C	P_D	305	W
		2.44	W/°C
Single Pulsed Avalanche Energy ^d	E_{AS}	380	mJ
Single Pulsed Avalanche Current ^d	I_{AS}	4.5	A
Operating and Store Temperature Range	T_J, T_{stg}	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Limit	Units
Thermal Resistance, Junction-to-Case	R_{JC}	0.41	°C/W
Thermal Resistance, Junction-to-Ambient	R_{JA}	62.5	°C/W



CEW46N65SF

Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	650			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = 650\text{V}, V_{\text{GS}} = 0\text{V}$		5		μA
Gate Body Leakage Current, Forward	I_{GSSF}	$V_{\text{GS}} = 30\text{V}, V_{\text{DS}} = 0\text{V}$		100		nA
Gate Body Leakage Current, Reverse	I_{GSSR}	$V_{\text{GS}} = -30\text{V}, V_{\text{DS}} = 0\text{V}$		-100		nA
On Characteristics^b						
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{GS}} = V_{\text{DS}}, I_D = 250\mu\text{A}$	2.5		4.5	V
Static Drain-Source On-Resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 10\text{V}, I_D = 20\text{A}$		49	58	$\text{m}\Omega$
Dynamic Characteristics^c						
Input Capacitance	C_{iss}	$V_{\text{DS}} = 100\text{V}, V_{\text{GS}} = 0\text{V}, f = 1\text{MHz}$		2300		pF
Output Capacitance	C_{oss}			120		pF
Reverse Transfer Capacitance	C_{rss}			10		pF
Switching Characteristics^c						
Turn-On Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{DD}} = 520\text{V}, I_D = 10\text{A}, V_{\text{GS}} = 10\text{V}, R_{\text{GEN}} = 10\Omega$		52		ns
Turn-On Rise Time	t_r			23		ns
Turn-Off Delay Time	$t_{\text{d}(\text{off})}$			176		ns
Turn-Off Fall Time	t_f			9		ns
Total Gate Charge	Q_g	$V_{\text{DS}} = 520\text{V}, I_D = 20\text{A}, V_{\text{GS}} = 10\text{V}$		92		nC
Gate-Source Charge	Q_{gs}			21		nC
Gate-Drain Charge	Q_{gd}			37		nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Current	I_S				46	A
Drain-Source Diode Forward Voltage ^b	V_{SD}	$V_{\text{GS}} = 0\text{V}, I_S = 20\text{A}$			1.5	V
Reverse Recovery Time	T_{rr}	$I_F = 20\text{A}, \text{di/dt} = 100\text{A/us}$		183		ns
Reverse Recovery Charge	Q_{rr}			1.2		μC
Peak Reverse Recovery Current	I_{rr}			12		A
Notes :						
a.Repetitive Rating : Pulse width limited by maximum junction temperature.						
b.Pulse Test : Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.						
c.Guaranteed by design, not subject to production testing.						
d.L = 37.5mH, $I_{\text{AS}} = 4.5\text{A}$, $V_{\text{DD}} = 60\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$.						




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Body Diode Forward Voltage Variation with Source Current




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area




Figure 9. Breakdown Voltage Variation VS Temperature




Figure 10. Switching Test Circuit




Figure 11. Switching Waveforms





Figure 12. Normalized Thermal Transient Impedance Curve

TO-247 產品外觀尺寸圖 (Product Outline Dimension)



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.830	5.210	0.190	0.205
A1	2.310	2.510	0.091	0.099
A2	1.900	2.160	0.075	0.085
b	1.140	1.400	0.045	0.055
b2	1.910	2.200	0.075	0.087
b4	2.960	3.160	0.117	0.124
C	0.590	0.800	0.023	0.031
D	20.800	21.340	0.819	0.840
e	5.45BSC		0.215BSC	
E	15.700	16.130	0.618	0.635
E2	4.320	5.100	0.170	0.201
E3	1.58	2.60	0.062	0.102
L	19.80	20.57	0.780	0.810
L1	3.81	4.32	0.150	0.170
ΦP	3.5	3.7	0.138	0.146
ΦP1	~	7.3	~	0.287
S	6.15BSC		0.242BSC	
Q	5.59	6.2	0.220	0.244