

P-Channel Enhancement Mode Field Effect Transistor

PRELIMINARY


FEATURES

- High power and current handling capability.
- Reliable and rugged.
- Pb-free lead plating ; RoHS compliant.
- Halogen Free.

APPLICATIONS

- DC-DC Converters.
- Load switch.
- Battery management.

V_{DS}	$R_{DS(ON)} \text{ typ } @V_{GS}$	I_D
-100V	$7.9\text{m}\Omega @ V_{GS} = -10\text{V}$	-151A



ABSOLUTE MAXIMUM RATINGS $T_C = 25^\circ\text{C}$ unless otherwise noted

Parameter		Symbol	Limit	Units
Drain-Source Voltage		V_{DS}	-100	V
Gate-Source Voltage		V_{GS}	± 20	V
Drain Current-Continuous	$I_D @ R_{\theta JC}$	$T_C = 25^\circ\text{C}$	-151	A
		$T_C = 70^\circ\text{C}$	-126	A
	$I_D @ R_{\theta JA}$	$T_A = 25^\circ\text{C}$	-12	A
		$T_A = 70^\circ\text{C}$	-10	A
Drain Current-Pulsed ^a	$I_{DM} @ R_{\theta JC}$	$T_C = 25^\circ\text{C}$	-604	A
	$I_{DM} @ R_{\theta JA}$	$T_A = 25^\circ\text{C}$	-48	A
Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$ - Derate above 25°C		P_D	454	W
			3.03	W/ $^\circ\text{C}$
Operating and Store Temperature Range		T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Limit	Units
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	0.33	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	50	$^\circ\text{C}/\text{W}$

Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS} = 0V, I_D = -250\mu A$	-100			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -100V, V_{GS} = 0V$			-1	μA
Gate Body Leakage Current, Forward	I_{GSSF}	$V_{GS} = 20V, V_{DS} = 0V$			100	nA
Gate Body Leakage Current, Reverse	I_{GSSR}	$V_{GS} = -20V, V_{DS} = 0V$			-100	nA
On Characteristics ^b						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS} = V_{DS}, I_D = -250\mu A$	-1		-3	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS} = -10V, I_D = -20A$		7.9	10	m Ω
		$V_{GS} = -4.5V, I_D = -15A$		8.5	11	m Ω
Gate Input Resistance	R_g	f=1MHz,open Drain		5		Ω
Dynamic Characteristics ^c						
Input Capacitance	C_{iss}	$V_{DS} = -50V, V_{GS} = 0V, f = 1MHz$		22150		pF
Output Capacitance	C_{oss}			2410		pF
Reverse Transfer Capacitance	C_{rss}			350		pF
Switching Characteristics ^c						
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = -50V, I_D = -15A, V_{GS} = -10V, R_{GEN} = 3.3\Omega$		45		ns
Turn-On Rise Time	t_r			19		ns
Turn-Off Delay Time	$t_{d(off)}$			828		ns
Turn-Off Fall Time	t_f			170		ns
Total Gate Charge	Q_g	$V_{DS} = -50V, I_D = -15A, V_{GS} = -10V$		570		nC
Gate-Source Charge	Q_{gs}			65		nC
Gate-Drain Charge	Q_{gd}			130		nC
Drain-Source Diode Characteristics and Maximun Ratings						
Drain-Source Diode Current-Continuous	I_S				-151	A
Drain-Source Diode Current-Pulsed ^b	I_{SM}				-604	A
Drain-Source Diode Forward Voltage ^b	V_{SD}	$V_{GS} = 0V, I_S = -10A$			-1.2	V
Notes : a.Repetitive Rating : Pulse width limited by maximum junction temperature. b.Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$. c.Guaranteed by design, not subject to production testing.						




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Body Diode Forward Voltage Variation with Source Current




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area




Figure 9. Breakdown Voltage Variation VS Temperature




Figure 10. On-Resistance VS Drain Current




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms





Figure 12. Normalized Thermal Transient Impedance Curve

TOLL 產品外觀尺寸圖 (Product Outline Dimension)



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.150	2.450	0.085	0.096
b	0.700	0.900	0.028	0.035
b1	9.650	9.950	0.380	0.392
c	0.400	0.600	0.016	0.024
D	10.180	10.580	0.401	0.417
D2	3.150	3.450	0.124	0.136
D4	4.400	4.700	0.173	0.185
E	9.700	10.100	0.382	0.398
E1	7.950	8.250	0.313	0.325
e	1.20BSC		0.047BSC	
H	11.480	11.880	0.452	0.468
H1	6.800	7.100	0.268	0.280
L	1.500	2.100	0.059	0.083
L1	0.500	0.900	0.020	0.035
L2	0.500	0.720	0.020	0.028
L3	1.000	1.300	0.039	0.051